# NSN 5950-00-412-2334

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-412-2334

# Reliability Indicator:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

## **Overall Height:**

2.500 inches

## **Frequency Rating:**

400.0 hertz single component

## Input-output Phase Relationship:

Three phase to six phase single component

## Transformer Winding Connection Type:

Delta-wye

#### Winding Shielding Method:

Internal shield grounded to inclosure and core single component

#### **Body Length:**

5.750 inches

#### Body Width:

5.250 inches

#### **Body Height:**

2.000 inches

#### Maximum Operating Temp:

70.0 degrees celsius

#### Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

### Winding Function And Quantity:

1 primary single component and 4 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

### Winding Operating Current:

4.3 amperes dc single component 3rd secondary

#### Winding Power Rating:

478.0 volts-amperes single component single primary

#### Winding Operating Voltage:

115.00 ac volts single component single primary

# NSN 5950-00-412-2334

Power Transformer - Page 2 of 2



**Thread Series Designator:** 

Unc single group

Terminal Type And Quantity:

31 solder stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0