# NSN 5950-00-412-2335

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-412-2335

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

#### **Overall Height:**

2.500 inches

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-delta

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

5.750 inches

#### **Body Width:**

5.250 inches

# **Maximum Operating Temp:**

70.0 degrees celsius

#### **Inclosure Type:**

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

#### **Features Provided:**

Tinned wire leads

## **Thread Size:**

0.164 inches single group

#### **Winding Operating Current:**

3.2 amperes dc single component 4th secondary

# Winding Power Rating:

326.0 volts-amperes single component single primary

#### **Winding Operating Voltage:**

38.40 ac volts single component 1st secondary

#### **Thread Series Designator:**

Unc single group

# NSN 5950-00-412-2335

Power Transformer - Page 2 of 2



<b>Terminal</b>	<b>Type</b>	And	Quantity:
-----------------	-------------	-----	-----------

15 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0