# NSN 5950-00-412-2335

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-412-2335

# **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

### **Overall Height:**

2.500 inches

#### **Frequency Rating:**

400.0 hertz single component

### Input-output Phase Relationship:

Three phase to three phase single component

### **Transformer Winding Connection Type:**

Delta-delta

#### Winding Shielding Method:

Internal shield grounded to inclosure and core single component

#### **Body Length:**

5.750 inches

#### **Body Width:**

5.250 inches

### Maximum Operating Temp:

70.0 degrees celsius

## Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

### Winding Function And Quantity:

1 primary single component and 4 secondary single component

#### **Features Provided:**

Tinned wire leads

#### **Thread Size:**

0.164 inches single group

### Winding Operating Current:

3.2 amperes dc single component 4th secondary

## Winding Power Rating:

326.0 volts-amperes single component single primary

## Winding Operating Voltage:

38.40 ac volts single component 1st secondary

# **Thread Series Designator:**

Unc single group

# NSN 5950-00-412-2335

Power Transformer - Page 2 of 2



# Terminal Type And Quantity:

15 solder stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0