

View Online at <https://aerobasegroup.com/nsn/5950-00-412-4284>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.297 inches single mounting facility single center group2.297 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.859 inches single mounting facility single center group1.859 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Core grounded single componentcore grounded single component

**Body Length:**

2.625 inches 2.625 inches

**Body Width:**

3.063 inches 3.063 inches

**Body Height:**

4.250 inches 4.250 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

3.0 amperes ac single component single secondary

**Winding Power Rating:**

121.5 volts-amperes single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary8.25 ac volts single component single secondary and 40.50 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0