

View Online at <https://aerobasegroup.com/nsn/5950-00-412-9596>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.890 inches single mounting facility single center group and 0.910 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.690 inches single mounting facility single center group and 0.710 inches single mounting facility single center group

Frequency Rating:

480.0 hertz single component

Winding Shielding Method:

Internal shield grounded to terminal single component

Body Length:

Between 1.390 inches and 1.410 inches

Body Width:

Between 1.320 inches and 1.340 inches

Body Height:

Between 0.990 inches and 1.010 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

200.0 milliamperes ac single component single secondary

Dc Resistance Rating In Ohms:

30.000 single component single primary

Winding Operating Voltage:

6.55 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0