

View Online at <https://aerobasegroup.com/nsn/5950-00-414-3088>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.560 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.755 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.620 inches

Body Width:

2.440 inches

Body Height:

5.370 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

3.4 amperes ac single component 1st secondary

Winding Operating Voltage:

400.00 ac volts single component single primary 30.00 ac volts single component 2nd secondary

Special Features:

One secondary winding is single phase

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0