

View Online at <https://aerobasegroup.com/nsn/5950-00-419-1462>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.810 inches single mounting facility single center group2.810 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 47.0 hertz single component and 63.0 hertz single component63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

Between 3.875 inches and 3.875 inches and 4.000 inches 4.000 inches

Body Width:

Between 3.495 inches and 3.495 inches and 3.620 inches 3.620 inches

Body Height:

Between 4.560 inches and 4.560 inches and 4.680 inches 4.680 inches

Inclosure Type:

Hermetically sealed with oilhermetically sealed with oil

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 6 secondary single component6 secondary single component

Thread Size:

0.112 inches single group0.112 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

32.00 ac volts single component 1st secondary15.00 ac volts single component 3rd secondary220.00 ac volts single component 2nd primary

Special Features:

2primary windings; six secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0