

View Online at <https://aerobasegroup.com/nsn/5950-00-419-3854>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.005 inches single mounting facility single center group3.005 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.255 inches single mounting facility single center group3.255 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase single componentthree phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

4.250 inches 4.250 inches

**Body Width:**

4.000 inches 4.000 inches

**Body Height:**

2.000 inches 2.000 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group32 single group

**Thread Size:**

0.190 inches single group0.190 inches single group

**Winding Operating Current:**

10.6 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

55.00 ac volts single component 2nd secondary26.00 ac volts single component 1st secondary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0