

View Online at <https://aerobasegroup.com/nsn/5950-00-419-3854>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.005 inches single mounting facility single center group3.005 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.255 inches single mounting facility single center group3.255 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single componentthree phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

4.250 inches 4.250 inches

Body Width:

4.000 inches 4.000 inches

Body Height:

2.000 inches 2.000 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

10.6 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

55.00 ac volts single component 2nd secondary26.00 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0