

View Online at <https://aerobasegroup.com/nsn/5950-00-419-5300>

Reliability Indicator:

Not establishednot established

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

0.780 inches 0.780 inches

Body Width:

0.580 inches 0.580 inches

Body Height:

0.550 inches 0.550 inches

Maximum Operating Temp:

120.0 degrees celsius120.0 degrees celsius

End Application:

Aircraft, prowler ea-6baircraft, prowler ea-6b

Inclosure Type:

Fully enclosedfully enclosed

Mounting Method:

Terminal single groupterminal single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Winding Operating Current:

3.0 milliamperes ac single component single secondary

Winding Operating Voltage:

2.82 ac volts single component single secondary10.80 ac volts single component single primary

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0