NSN 5950-00-419-5311

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-419-5311

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mountin |
| 2.125 inches single mounting facility single cen |
| Center To Center Distance Between Mountin |
| 1 750 inches single mounting facility single cen |

ng Facilities Parallel To Length:

iter group

ng Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.750 inches

Body Width:

2.380 inches

Body Height:

2.810 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.7 amperes ac single component 2nd secondary

Winding Operating Voltage:

72.00 ac volts single component 3rd secondary33.00 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

NSN 5950-00-419-5311

Power Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0