

View Online at <https://aerobasegroup.com/nsn/5950-00-419-5312>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

Overall Height:

4.060 inches 4.060 inches

Mounting Hole Diameter:

0.172 inches single group0.172 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

2.750 inches 2.750 inches

Body Width:

2.380 inches 2.380 inches

Maximum Operating Temp:

26.5 degrees celsius26.5 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

Winding Operating Current:

600.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

34.00 ac volts single component 2nd secondary240.00 ac volts single component 1st secondary

Special Features:

1primary winding and five secondary windings

Terminal Type And Quantity:

13 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0