

View Online at <https://aerobasegroup.com/nsn/5950-00-419-5312>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

**Overall Height:**

4.060 inches 4.060 inches

**Mounting Hole Diameter:**

0.172 inches single group0.172 inches single group

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

2.750 inches 2.750 inches

**Body Width:**

2.380 inches 2.380 inches

**Maximum Operating Temp:**

26.5 degrees celsius26.5 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

**Winding Operating Current:**

600.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

34.00 ac volts single component 2nd secondary240.00 ac volts single component 1st secondary

**Special Features:**

1primary winding and five secondary windings

**Terminal Type And Quantity:**

13 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0