

View Online at <https://aerobasegroup.com/nsn/5950-00-419-7536>

Reliability Indicator:

Not establishednot established

Mounting Hole Diameter:

0.125 inches single group0.125 inches single group

Frequency Rating:

380.0 hertz single component and 380.0 hertz single component and 420.0 hertz single component420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

1.900 inches 1.900 inches

Body Width:

1.560 inches 1.560 inches

Body Height:

1.570 inches 1.570 inches

Maximum Operating Temp:

120.0 degrees celsius120.0 degrees celsius

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group1.250 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Winding Operating Current:

1.3 amperes ac single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary6.30 ac volts single component 1st secondary

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0