

View Online at <https://aerobasegroup.com/nsn/5950-00-419-7539>

**Reliability Indicator:**

Not establishednot established

**Frequency Rating:**

400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single componentinternal shield grounded to core single component

**Body Length:**

0.830 inches 0.830 inches

**Body Width:**

0.800 inches 0.800 inches

**Body Height:**

1.080 inches 1.080 inches

**Maximum Operating Temp:**

120.0 degrees celsius120.0 degrees celsius

**Inclosure Type:**

Fully enclosedfully enclosed

**Mounting Facility Quantity:**

2 single group2 single group

**Mounting Method:**

Threaded hole single groupthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

**Thready Qty Per Inch (tpi):**

40 single group40 single group

**Thread Size:**

0.112 inches single group0.112 inches single group

**Winding Operating Current:**

3.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

115.00 ac volts single component single primary36.00 ac volts single component single secondary36.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

4 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0