

View Online at <https://aerobasegroup.com/nsn/5950-00-419-7540>

Reliability Indicator:

Not establishednot established

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

0.950 inches 0.950 inches

Body Width:

0.950 inches 0.950 inches

Body Height:

0.800 inches 0.800 inches

Distance Between Mounting Facility Centers:

0.660 inches single mounting facility single center group0.660 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

40 single group40 single group

Thread Size:

0.112 inches single group0.112 inches single group

Winding Operating Current:

400.0 milliamperes ac single component single secondary

Winding Operating Voltage:

7.00 ac volts single component single primary and 13.00 ac volts single component single primary and 26.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0