

View Online at <https://aerobasegroup.com/nsn/5950-00-419-7615>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.281 inches single mounting facility single center group and 3.281 inches single mounting facility single center group and 3.344 inches single mounting facility single center group3.344 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.656 inches single mounting facility single center group and 2.656 inches single mounting facility single center group and 2.719 inches single mounting facility single center group2.719 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

4.312 inches 4.312 inches

Body Width:

3.688 inches 3.688 inches

Body Height:

4.500 inches 4.500 inches

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Operating Voltage:

19.00 ac volts single component single secondary1 15.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0