NSN 5950-00-419-8417

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-419-8417

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.000 inches single mounting facility single center group
Mounting Hole Diameter:
0.313 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Body Length:
5.500 inches
Body Width:
4.500 inches
Body Height:
7.750 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
4 single group Mounting Method:
Mounting Method:
Mounting Method: Flange single group and unthreaded hole single group
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug Shelf Life:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug Shelf Life: N/a
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug Shelf Life: N/a
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug Shelf Life: N/a Unit Of Measure:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 5 secondary single component Terminal Type And Quantity: 19 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No