# NSN 5950-00-419-9663

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-419-9663

# **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

4.380 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

#### **Overall Height:**

7.625 inches

#### **Frequency Rating:**

47.0 hertz single component and 63.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Delta-wye

#### **Winding Shielding Method:**

Internal shield brought out to terminal single component

#### **Body Length:**

4.880 inches

# **Body Width:**

3.000 inches

# **Body Height:**

7.125 inches

#### **Maximum Operating Temp:**

115.0 degrees celsius

# **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

8 single group

#### **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

# Thready Qty Per Inch (tpi):

32 single group

# Thread Size:

0.138 inches single group

# **Winding Operating Current:**

450.0 milliamperes dc single component single secondary

# **Winding Operating Voltage:**

200.00 ac volts single component single primary and 380.00 ac volts single component single secondary220.00 ac volts single component single primary and 240.00 ac volts single component single primary

#### **Thread Series Designator:**

Unc single group

# NSN 5950-00-419-9663

Power Transformer - Page 2 of 2



Terminal Type And Quantity:
17 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0