## NSN 5950-00-419-9896

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-419-9896

| Reliability Indicator:                                       |
|--|
| Not established  |
| Overall Length:  |
| 5.625 inches   |
| Frequency Rating:  |
| 50.0 hertz single component and 400.0 hertz single component |
| Input-output Phase Relationship:                             |
| Single phase to single phase single component                |
| Winding Shielding Method:                                    |
| Internal shield brought out to terminal single component     |
| Body Length:   |
| 5.000 inches   |
| Body Width:  |
| 4.625 inches   |
| Body Height:   |
| 6.250 inches   |
| Distance Between Mounting Facility Centers:                  |
| 3.500 inches single mounting facility single center group    |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:                                  |
| 2 single group   |
| Mounting Method:   |
| Threaded hole single group                                   |
| Winding Function And Quantity:                               |
| 2 primary single component and 12 secondary single component |
| Thready Qty Per Inch (tpi):                                  |
| 20 single group  |
| Thread Size:   |
| 0.250 inches single group                                    |
| Thread Series Designator:                                    |
| Unc single group   |
| Terminal Type And Quantity:                                  |
| 29 turret  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| Fiig:<br>A058b0  |
| A03000   |
|  |