

View Online at <https://aerobasegroup.com/nsn/5950-00-421-6260>

**Reliability Indicator:**

Not establishednot establishednot established

**Mounting Hole Diameter:**

0.156 inches single group0.156 inches single group0.156 inches single group

**Frequency Rating:**

50.0 hertz single component50.0 hertz single component50.0 hertz single component

**Input-output Phase Relationship:**

Three phase to two phase single componentthree phase to two phase single componentthree phase to two phase single component

**Transformer Winding Connection Type:**

Scottscottscott

**Body Length:**

Between 2.195 inches and 2.195 inches and 2.195 inches and 2.205 inches 2.205 inches 2.205 inches

**Body Width:**

Between 1.096 inches and 1.096 inches and 1.096 inches and 1.106 inches 1.106 inches 1.106 inches

**Body Height:**

Between 0.595 inches and 0.595 inches and 0.595 inches and 0.605 inches 0.605 inches 0.605 inches

**Maximum Operating Temp:**

125.0 degrees celsius125.0 degrees celsius125.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.100 inches single mounting facility single center group1.100 inches single mounting facility single center group1.100 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosedfully enclosedfully enclosed

**Mounting Facility Quantity:**

2 single group2 single group2 single group

**Mounting Method:**

Unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component2 secondary single component

**Winding Operating Voltage:**

26.00 ac volts single component 1st secondary11.80 ac volts single component single primary11.80 ac volts single component single primary

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0