

View Online at <https://aerobasegroup.com/nsn/5950-00-421-6260>

Reliability Indicator:

Not establishednot establishednot established

Mounting Hole Diameter:

0.156 inches single group0.156 inches single group0.156 inches single group

Frequency Rating:

50.0 hertz single component50.0 hertz single component50.0 hertz single component

Input-output Phase Relationship:

Three phase to two phase single componentthree phase to two phase single componentthree phase to two phase single component

Transformer Winding Connection Type:

Scottscottscott

Body Length:

Between 2.195 inches and 2.195 inches and 2.195 inches and 2.205 inches 2.205 inches 2.205 inches

Body Width:

Between 1.096 inches and 1.096 inches and 1.096 inches and 1.106 inches 1.106 inches 1.106 inches

Body Height:

Between 0.595 inches and 0.595 inches and 0.595 inches and 0.605 inches 0.605 inches 0.605 inches

Maximum Operating Temp:

125.0 degrees celsius125.0 degrees celsius125.0 degrees celsius

Distance Between Mounting Facility Centers:

1.100 inches single mounting facility single center group1.100 inches single mounting facility single center group1.100 inches single mounting facility single center group

Inclosure Type:

Fully enclosedfully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group2 single group

Mounting Method:

Unthreaded hole single groupunthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component2 secondary single component

Winding Operating Voltage:

26.00 ac volts single component 1st secondary11.80 ac volts single component single primary11.80 ac volts single component single primary

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0