

View Online at <https://aerobasegroup.com/nsn/5950-00-421-9744>

Reliability Indicator:

Not established

Overall Length:

2.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.677 inches single mounting facility single center group and 1.697 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.427 inches single mounting facility single center group and 1.447 inches single mounting facility single center group

Overall Height:

3.545 inches

Overall Width:

2.062 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Voltage:

8.25 ac volts single component 2nd secondary and 108.00 ac volts single component single primary and 115.00 ac volts single component single primary and 12.00 ac volts single component 2nd secondary 122.00 ac volts single component single primary

Test Data Document:

10001-1569243 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0