

View Online at <https://aerobasegroup.com/nsn/5950-00-422-1448>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

3.720 inches

**Body Width:**

2.690 inches

**Body Height:**

2.310 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Operating Current:**

600.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

112.00 ac volts single component 2nd secondary 115.00 ac volts single component single primary 6.30 ac volts single component 3rd secondary

**Test Data Document:**

93024-300064-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0