

View Online at <https://aerobasegroup.com/nsn/5950-00-422-3476>

Reliability Indicator:

Not establishednot establishednot established

Overall Length:

4.125 inches 4.125 inches 4.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group3.438 inches single mounting facility single center group3.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Overall Height:

3.438 inches 3.438 inches 3.438 inches

Overall Width:

3.375 inches 3.375 inches 3.375 inches

Mounting Slot Width:

0.196 inches single group0.196 inches single group0.196 inches single group

Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Inclosure Type:

Openopenopen

Mounting Facility Quantity:

4 single group4 single group4 single group

Mounting Method:

Flange single group and flange single group and flange single group and slot single groupslot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component2 secondary single component

Winding Operating Current:

4.0 amperes ac single component all secondary

Winding Power Rating:

136.0 volts-amperes single component all secondary136.0 volts-amperes single component all secondary

Winding Operating Voltage:

115.00 ac volts single component single primary34.00 ac volts single component all secondary34.00 ac volts single component all secondary

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization: