NSN 5950-00-422-5356

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-422-5356

Reliability Indicator:

Not establishednot established

Frequency Rating:

3.8 kilohertz single component3.8 kilohertz single component3.8 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component component

Body Length:

45.0 millimeters 45.0 millimeters 45.0 millimeters

Body Width:

45.0 millimeters 45.0 millimeters 45.0 millimeters

Body Height:

33.0 millimeters 33.0 millimeters 33.0 millimeters

Distance Between Mounting Facility Centers:

32.7 millimeters single mounting facility single center group and 32.7 millimeters single mounting facility single center group and 32.7 millimeters single mounting facility single center group 33.3 millimeters single mounting facility single cente

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

2 single group2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 3 secondary single component3 secondary single component

Thread Size:

3.0 millimeters single group3.0 millimeters single group3.0 millimeters single group

Winding Operating Current:

15.0 milliamperes ac single component single primary

Winding Operating Voltage:

795.00 ac volts single component 1st secondary6.67 ac volts single component 3rd secondary6.67 ac volts single component 2nd secondary

Thread Series Designator:

Iso m single group

Terminal Type And Quantity:

10 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

.