

View Online at <https://aerobasegroup.com/nsn/5950-00-422-5357>

Reliability Indicator:

Not establishednot establishednot establishednot established

Frequency Rating:

3.7 kilohertz single component3.7 kilohertz single component3.7 kilohertz single component3.7 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component

Body Length:

45.0 millimeters 45.0 millimeters 45.0 millimeters 45.0 millimeters

Body Width:

45.0 millimeters 45.0 millimeters 45.0 millimeters 45.0 millimeters

Body Height:

33.0 millimeters 33.0 millimeters 33.0 millimeters 33.0 millimeters

Distance Between Mounting Facility Centers:

32.8 millimeters single mounting facility single center group and 32.8 millimeters single mounting facility single center group and 32.8 millimeters single mounting facility single center group and 32.8 millimeters single mounting facility single center group and 33.2 millimeters single mounting facility single center group33.2 millimeters single mounting facility single center group33.2 millimeters single mounting facility single center group33.2 millimeters single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealedhermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single groupthreaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component1 secondary single component1 secondary single component

Thread Size:

3.0 millimeters single group3.0 millimeters single group3.0 millimeters single group3.0 millimeters single group

Winding Operating Current:

21.5 milliamperes ac single component single secondary

Winding Operating Voltage:

209.00 ac volts single component single primary and 378.00 ac volts single component single secondary378.00 ac volts single component single secondary220.00 ac volts single component single primary and 231.00 ac volts single component single primary

Thread Series Designator:

Iso m single group

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: