# NSN 5950-00-422-5369

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-422-5369

_								
D		lia	hi	liŧv,	Ind	lica	ıŧα	r.
	<b>C</b>	на	v	HLV	IIIU	1160	ıv	ι.

Not establishednot established

### **Overall Length:**

40.2 millimeters 40.2 millimeters

# Center To Center Distance Between Mounting Facilities Parallel To Length:

20.12 millimeters single mounting facility single center group and 20.12 millimeters single mounting facility single center group and 20.52 millimeters single mounting facility single center group 20.52 millimeters single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

25.2 millimeters single mounting facility single center group and 25.2 millimeters single mounting facility single center group and 25.6 millimeters single mounting facility single center group 25.6 millimeters single mounting facility single center group

#### **Overall Height:**

30.65 millimeters 30.65 millimeters

#### **Overall Width:**

31.2 millimeters 31.2 millimeters

#### Frequency Rating:

3.75 kilohertz single component3.75 kilohertz single component

### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

# **Maximum Operating Temp:**

130.0 degrees celsius 130.0 degrees celsius

# Inclosure Type:

Fully enclosedfully enclosed

### **Mounting Method:**

Terminal single groupterminal single group

# **Winding Function And Quantity:**

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

# **Features Provided:**

Tinned wire leads

#### **Winding Operating Voltage:**

18.00 ac volts single component all primary

# **Terminal Type And Quantity:**

8 pin

# Shelf Life:

N/a

### **Unit Of Measure:**

**Demilitarization:** 

No

# Fiig:

A058b0