NSN 5950-00-422-5369

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-422-5369

_								
D	\sim	lia	hi	litv,	Ind	lica	+~	
Г		на	IJΙ	IILV	IIIU	III	ιU	Ι.

Not establishednot established

Overall Length:

40.2 millimeters 40.2 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

20.12 millimeters single mounting facility single center group and 20.12 millimeters single mounting facility single center group and 20.52 millimeters single mounting facility single center group 20.52 millimeters single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

25.2 millimeters single mounting facility single center group and 25.2 millimeters single mounting facility single center group and 25.6 millimeters single mounting facility single center group 25.6 millimeters single mounting facility single center group

Overall Height:

30.65 millimeters 30.65 millimeters

Overall Width:

31.2 millimeters 31.2 millimeters

Frequency Rating:

3.75 kilohertz single component3.75 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius 130.0 degrees celsius

Inclosure Type:

Fully enclosedfully enclosed

Mounting Method:

Terminal single groupterminal single group

Winding Function And Quantity:

2 primary single component and 2 primary single component and 2 secondary single component2 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Voltage:

18.00 ac volts single component all primary

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0