

View Online at <https://aerobasegroup.com/nsn/5950-00-422-8577>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.687 inches single mounting facility single center group3.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.687 inches single mounting facility single center group3.687 inches single mounting facility single center group

Frequency Rating:

55.0 hertz single component and 55.0 hertz single component and 480.0 hertz single component480.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

4.375 inches 4.375 inches

Body Width:

5.000 inches 5.000 inches

Body Height:

5.250 inches 5.250 inches

Inclosure Type:

Partially enclosed, double shellpartially enclosed, double shell

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Threaded hole single groupthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thready Qty Per Inch (tpi):

32 single group32 single group

Thread Size:

0.190 inches single group0.190 inches single group

Winding Operating Current:

19.5 amperes ac single component single secondary

Winding Operating Voltage:

21.80 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0