NSN 5950-00-422-8579

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-422-8579

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.375 inches single mounting facility single center group |
| Overall Height: |
| 4.375 inches |
| Overall Width: |
| 4.500 inches |
| Mounting Hole Diameter: |
| 0.125 inches single group |
| Frequency Rating: |
| 47.0 hertz single component and 63.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| External inclosure single component |
| Body Length: |
| 5.250 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 2 primary single component and 1 secondary single component |
| Winding Operating Voltage: |
| 200.00 ac volts single component 2nd primary and 100.00 ac volts single component 1st primary and 250.00 ac volts single component |
| 2nd primary125.00 ac volts single component 1st primary |
| Terminal Type And Quantity: |
| 15 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |