

View Online at <https://aerobasegroup.com/nsn/5950-00-424-9150>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.370 inches single mounting facility single center group and 1.380 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.807 inches single mounting facility single center group and 0.817 inches single mounting facility single center group

Impedance Rating In Ohms:

400.0 single component single primary

Frequency Rating:

1.0 kilohertz single component and 10.0 kilohertz single component

Maximum Transformer Power Rating:

5.0 watts single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.750 inches

Body Width:

1.250 inches

Body Height:

1.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

50.0 milliamperes dc single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0