## NSN 5950-00-426-2675

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-426-2675

## **Reliability Indicator:**

Not establishednot establishednot established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group2.297 inches single mounting facility single center group2.297 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group1.859 inches single mounting facility single center group1.859 inches single mounting facility single center group

## Frequency Rating:

50.0 hertz single component or 50.0 hertz single component or 50.0 hertz single component or 60.0 hertz single component or 60.0 hertz single component or 50.0 hertz single component or

#### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single componentsingle phase to single phase single component component

### **Body Length:**

3.063 inches 3.063 inches 3.063 inches

### **Body Width:**

2.625 inches 2.625 inches 2.625 inches

## **Body Height:**

4.250 inches 4.250 inches 4.250 inches

## **Maximum Operating Temp:**

50.0 degrees celsius50.0 degrees celsius50.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed with oilhermetically sealed with oilhermetically sealed with oil

## **Mounting Facility Quantity:**

4 single group4 single group4 single group

## **Mounting Method:**

Threaded stud single groupthreaded stud single groupthreaded stud single group

#### Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 primary single component and 5 secondary single component5 secondary single component

## Thread Size:

0.164 inches single group0.164 inches single group0.164 inches single group

### **Winding Operating Current:**

600.0 milliamperes dc single component 4th secondary

## Winding Operating Voltage:

35.00 dc volts single component 3rd secondary35.00 dc volts single component 3rd secondary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

15 turret

#### Shelf Life:

N/a

## **Unit Of Measure:**

# NSN 5950-00-426-2675

Power Transformer - Page 2 of 2



Fiig:

A058b0