## NSN 5950-00-426-4349

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-426-4349

view Offiline at https://acrobasegroup.com/nsi//3330-00-420-4343
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.812 inches single mounting facility single center group
Frequency Rating:
45.0 hertz single component and 440.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
7.250 inches
Body Width:
3.438 inches
Body Height:
2.938 inches
Inclosure Type:
Partially enclosed, double shell
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Voltage:
118.00 ac volts single component single primary
Thread Series Designator:
Unf single group
Terminal Type And Quantity:
9 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5950-00-426-4349

Power Transformer - Page 2 of 2



Fiig:

A058b0