

View Online at <https://aerobasegroup.com/nsn/5950-00-426-5768>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.151 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.565 inches and 3.595 inches

Body Width:

Between 2.605 inches and 2.635 inches

Body Height:

Between 1.615 inches and 1.645 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

84.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

200.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

10 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0