NSN 5950-00-426-9602

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-426-9602

	_					_				
ı	D	ام	li a	hi	ilitv	· In	di	cat	-	r.
ı	\mathbf{r}	CI	па	v	IIILV	- 111	uı	Lai	LUI	١.

Not establishednot established

Overall Length:

1.406 inches 1.406 inches

Overall Height:

1.406 inches 1.406 inches

Overall Width:

1.000 inches 1.000 inches

Mounting Slot Width:

0.125 inches single group 0.125 inches single group

Frequency Rating:

2.0 kilohertz single component and 2.0 kilohertz single component and 150.0 kilohertz single component 150.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Maximum Operating Temp:

145.0 degrees celsius145.0 degrees celsius

Distance Between Mounting Facility Centers:

1.094 inches single mounting facility single center group and 1.094 inches single mounting facility single center group and 1.219 inches single mounting facility single center group and 1.219 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Flange single group and flange single group and slot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

19.0 microamperes ac single component single secondary

Winding Operating Voltage:

8.00 ac volts single component single secondary8.00 ac volts single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0