

View Online at <https://aerobasegroup.com/nsn/5950-00-428-3341>

**Reliability Indicator:**

Not establishednot established

**Frequency Rating:**

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

**Body Length:**

3.500 inches 3.500 inches

**Body Width:**

3.000 inches 3.000 inches

**Body Height:**

2.060 inches 2.060 inches

**Inclosure Type:**

Fully enclosedfully enclosed

**Winding Function And Quantity:**

2 primary single component and 2 primary single component and 5 secondary single component5 secondary single component

**Features Provided:**

Color coded lead

**Winding Operating Current:**

500.0 milliamperes dc single component 3rd secondary

**Winding Operating Voltage:**

9.01 ac volts single component 4th secondary and 18.96 ac volts single component 1st secondary and 18.56 ac volts single component 4th secondary19.74 ac volts single component 1st secondary

**Special Features:**

2 primaries, 5 secondaries; all output currents are stated as rectified; primaries may be strapped for 230 volt operation

**Terminal Type And Quantity:**

17 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0