

View Online at <https://aerobasegroup.com/nsn/5950-00-428-3341>

Reliability Indicator:

Not establishednot established

Frequency Rating:

50.0 hertz single component and 50.0 hertz single component and 400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single componentinternal shield grounded to inclosure single component

Body Length:

3.500 inches 3.500 inches

Body Width:

3.000 inches 3.000 inches

Body Height:

2.060 inches 2.060 inches

Inclosure Type:

Fully enclosedfully enclosed

Winding Function And Quantity:

2 primary single component and 2 primary single component and 5 secondary single component5 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

500.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

9.01 ac volts single component 4th secondary and 18.96 ac volts single component 1st secondary and 18.56 ac volts single component 4th secondary19.74 ac volts single component 1st secondary

Special Features:

2 primaries, 5 secondaries; all output currents are stated as rectified; primaries may be strapped for 230 volt operation

Terminal Type And Quantity:

17 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0