NSN 5950-00-429-7163

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-429-7163 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.688 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.438 inches single mounting facility single center group |
| Frequency Rating: |
| 400.0 hertz single component |
| nput-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.312 inches |
| Body Width: |
| 2.062 inches |
| Body Height: |
| 3.250 inches |
| nclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Voltage: |
| 115.00 ac volts single component single primary12.00 ac volts single component single secondary and 14.00 ac volts single component |
| single secondary and 16.40 ac volts single component single secondary and 18.80 ac volts single component single secondary and 21.20 |
| ac volts single component single secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 9 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| |

Fiig: A058b0