

View Online at <https://aerobasegroup.com/nsn/5950-00-429-9992>

Reliability Indicator:

Not established

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.313 inches

Body Width:

1.313 inches

Body Height:

1.750 inches

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

8.5 milliamperes ac single component single secondary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single secondary

Test Data Document:

53711-5190987 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0