NSN 5950-00-430-0678

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-430-0678

_			
R۵	liahi	litv	Indicator:
ĸe	IIabi	IILV	mulcator.

Not establishednot established

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Body Length:

1.375 inches 1.375 inches

Body Outside Diameter:

1.375 inches 1.375 inches

Maximum Operating Temp:

110.0 degrees celsius110.0 degrees celsius

Distance Between Mounting Facility Centers:

1.000 inches single mounting facility single center group1.000 inches single mounting facility single center group

Inclosure Type:

Hermetically sealedhermetically sealed

Mounting Facility Quantity:

2 single group2 single group

Mounting Method:

Threaded stud single groupthreaded stud single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

Thread Size:

0.164 inches single group 0.164 inches single group

Winding Operating Current:

960.0 milliamperes ac single component single secondary

Winding Operating Voltage:

26.00 ac volts single component single secondary115.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0