

View Online at <https://aerobasegroup.com/nsn/5950-00-430-6282>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group2.125 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group0.188 inches single group

Frequency Rating:

60.0 hertz single component60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single componentinternal shield grounded to core single component

Body Length:

3.000 inches 3.000 inches

Body Width:

2.625 inches 2.625 inches

Body Height:

3.062 inches 3.062 inches

Inclosure Type:

Openopen

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and slot single groupslot single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

Winding Operating Voltage:

32.20 ac volts single component 1st secondary11.00 ac volts single component 2nd secondary and 12.40 ac volts single component 2nd secondary and 13.50 ac volts single component 2nd secondary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0