

View Online at <https://aerobasegroup.com/nsn/5950-00-431-3197>

Reliability Indicator:

Not established

Inductance Rating:

5.60 microhenries single component single winding

Coil Form Type:

Solid single component

Core Construction:

Powdered single component

Body Length:

Between 0.365 inches and 0.385 inches

Body Outside Diameter:

Between 0.146 inches and 0.166 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

Landing craft air cushion (lcac); sturgeon class ssn (637); virginia class cgn (41); los angeles class ssn (688); ticonderoga class cg (47); radar, series an/sps-4 (v); forrestal class cv; spruance class dd (963) ; nimitz class cvn

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding

Features Provided:

Tinned wire leads

Winding Operating Current:

495.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

0.320 single component single winding

Quality Factor:

45 single component single winding

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0