

View Online at <https://aerobasegroup.com/nsn/5950-00-431-3619>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase single component

**Winding Shielding Method:**

Core grounded and brought out to terminal single component

**Body Length:**

3.870 inches

**Body Width:**

3.220 inches

**Body Height:**

2.760 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

600.0 milliamperes ac single component 1st secondary

**Winding Power Rating:**

52.13 volts-amperes single component 2nd secondary3.6 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

6.00 ac volts single component 1st secondary47.20 ac volts single component 3rd secondary34.75 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0