

View Online at <https://aerobasegroup.com/nsn/5950-00-431-3619>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Winding Shielding Method:

Core grounded and brought out to terminal single component

Body Length:

3.870 inches

Body Width:

3.220 inches

Body Height:

2.760 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 1st secondary

Winding Power Rating:

52.13 volts-amperes single component 2nd secondary3.6 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.00 ac volts single component 1st secondary47.20 ac volts single component 3rd secondary34.75 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0