# NSN 5950-00-431-8482

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-431-8482

# **Reliability Indicator:**

Not establishednot established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.800 inches single mounting facility single center group2.800 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single componentthree phase to three phase single component

#### **Body Length:**

4.300 inches 4.300 inches

#### **Body Width:**

3.812 inches 3.812 inches

#### **Body Height:**

2.500 inches 2.500 inches

#### **Inclosure Type:**

Fully enclosedfully enclosed

#### **Mounting Facility Quantity:**

4 single group4 single group

## **Mounting Method:**

Threaded hole single groupthreaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 1 secondary single component1 secondary single component

## Thready Qty Per Inch (tpi):

32 single group32 single group

# Thread Size:

0.164 inches single group 0.164 inches single group

#### **Winding Operating Current:**

1.0 amperes ac single component single secondary

# Winding Operating Voltage:

199.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

8 tab, solder lug

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-431-8482

Power Transformer - Page 2 of 2



Fiig:

A058b0