

View Online at <https://aerobasegroup.com/nsn/5950-00-432-5869>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.300 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.800 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.650 inches

Body Width:

1.125 inches

Body Height:

1.125 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 7 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

8.8 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

75.00 ac volts single component 3rd secondary 102.50 ac volts single component all primary 6.30 ac volts single component 4th secondary

Special Features:

Primary windings; 7 secondary windings; secondary windings six and seven have center taps

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0