

View Online at <https://aerobasegroup.com/nsn/5950-00-432-5869>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.300 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.800 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

2.650 inches

**Body Width:**

1.125 inches

**Body Height:**

1.125 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

2 primary single component and 7 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

8.8 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

75.00 ac volts single component 3rd secondary102.50 ac volts single component all primary6.30 ac volts single component 4th secondary

**Special Features:**

Primary windings; 7secondary windings; secondary windings six and seven have center taps

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

20 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0