NSN 5950-00-432-5928

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-432-5928
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.438 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.938 inches
Body Width:
3.375 inches
Body Height:
4.313 inches
Maximum Operating Temp:
65.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Cooling Method:
Self-cooled
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
200.0 milliamperes ac single component single secondary
Winding Operating Voltage:
115.00 ac volts single component single primary267.30 ac volts single component single secondary and 282.15 ac volts single componen
single secondary and 297.00 ac volts single component single secondary and 311.85 ac volts single component single secondary and
326.70 ac volts single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:

N/a

9 pin Shelf Life:

NSN 5950-00-432-5928

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0