NSN 5950-00-432-7655

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-432-7655

view Offiline at https://acrobasegroup.com/hish/0900-00-402-7000							
Reliability Indicator:							
Not established							
Center To Center Distance Between Mounting Facilities Parallel To Length:							
1.188 inches single mounting facility single center group							
Center To Center Distance Between Mounting Facilities Parallel To Width:							
1.188 inches single mounting facility single center group							
Inductance Type:							
Swinging							
Inductance Rating:							
0.80 millihenries single component single winding and 3.20 millihenries single component single winding							
Frequency Rating:							
90.0 hertz single component and 840.0 hertz single component							
Body Length:							
2.375 inches							
Body Width:							
1.625 inches							
Body Height:							
1.625 inches							
Winding Quantity:							
1 single component							
Inclosure Type:							
Hermetically sealed							
Mounting Facility Quantity:							
4 single group							
Mounting Method:							
Threaded hole single group							
Rating Method:							
Electrical single component single winding							
Thready Qty Per Inch (tpi):							
32 single group							
Thread Size:							
0.138 inches single group							
Winding Operating Current:							
1.0 amperes dc single component single winding and 10.0 amperes dc single component single winding							
Dc Resistance Rating In Ohms:							

0.100 single component single winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

NSN 5950-00-432-7655

Reactor - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A058b0